

DGIN 5201 Digital Transformation Lecture 7

Lec 5: Back-end Processing

Vlado Keselj

Time and date: 13:05–14:25, 21-Jan-2025

Location: LSC C236

Image: DALL-E. Bing Image Creator. Generated by AI

Previous Lecture

- Notices: Lab 1 deadline postponed, Emacs notes
- Example e3:
 - Simple password protection in Apache
 - Concepts review: rsync, htpasswd, .htaccess
- Unix-style customization
 - Text-based customizations
 - Examples: Bash, Emacs, Apache
- Example e4:
 - HTML form and form fields
 - Concepts review: form, text field, drop-down list

Back-end Processing

- How to
 - receive data at the server end from the client (browser)
 - process data and send some results back to the client
- This is called Back-end processing
- Some options to implement:
 - Apache has a way to help:
 - ⋆ CGI Common Gateway Interface
 - Use a server: build one or use server-based options

CGI Processing

- CGI Common Gateway Interface
- Implemented as CGI program; e.g.: prog.cgi
- When requested, executed by Web server and output returned
- Input prepared by Web server

Example e5: Backend Server Processing using CGI

- Using rsync copy e4 to e5
- Let us first check that CGI scripts are working by creating file test.cgi in e5 as follows:

```
#!/usr/bin/perl
use CGI qw/:standard/;
print header;
print "<html><body>Test\n";
```

- The file should be user executable, without permissions to the group and others (rwx-----)
- Run the command ./test.cgi and you should get a simple output as follows:

```
Content-Type: text/html; charset=ISO-8859-1
<html><body>Test
```

• Check in browser: https://web.cs.dal.ca···dgin5201/e5/test.cgi

Perl Scripting Language

- What we saw in test.cgi program is example of a Perl program
- Perl is a scripting language, similar to Python and PHP
- Provides convenient and quick data preprocessing
- Text processing oriented
- Appropriate for rapid prototyping, and CGI programming

Example e5: Preparing form for processing

Modify index.html the table part:

```
<form method="post" action="register.cgi">
First and last name:
<input type="text" name="name">
Email:
<input type="text" name="email">
Certificate (DB, HI, DS):
<select name="certificate">
 <option>DB</option><option>HI</option>
 <option>DS</option></select>
<input type="submit" value="Submit"/>
</form>
```

7 / 13

Example e5: Processing Data

• Prepare user executable file register.cgi:

```
#!/usr/bin/perl
use CGI qw/:standard/;
print header;
print "<html><body><h1>Registration</h1>\n";
print "The following registration is received:\n";
$name = param('name');  $email = param('email');
$certificate = param('certificate');
print <<"EOT";</pre>
First and last name:
$name
Email:$email
Certificate (DB, HI, DS):$certificate
align=center colspan=2>
<a href="index.html">Back to Registration Page</a>
EOT
```

Example e5: Processing Data and Testing

- Submit some registrations and make sure register.cgi works well
- This completes Example e5

Concepts Review: Example e5

- Server-side processing, concept of CGI (Common Gateway Interface)
- Perl programming language, Perl with CGI
- o <form method="post" action="...">
- <input ... name="x">
- <input type="submit" value="Submit/>
- CGI processing in Perl

Example e6: Saving Registration Data: Implementation

- Using rsync copy e5 to e6; adjust .htaccess
- To save registration, add the following line in the script register.cgi:

```
$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\exintet{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$\text{$
```

• and we add the following function at the end of the program:

```
sub save_registration {
  my ($name, $email, $certificate) = @_;
  open (my $fh, ">>registrations-saved.txt") or die;
  print $fh "\nname: $name\nemail: $email\n".
    "certificate: $certificate\n";
  close($fh);
}
```

Example e6: Saving Registration Data: Testing

- First check syntax: perl -c register.cgi
- Test the web site by making several registrations
- Check that registrations are saved in the file registrations-saved.txt
- Check permissions of registrations-saved.txt
 - ▶ If not all-readable, make them all-readable
 - Verify that the file is accessible on the web (!)
- Change the permissions of registrations-saved.txt to user-only readable and writeable
- Check accessibility on the web; Lesson learned!
- Check that the application still works

Concepts Review: Example e6

- Perl subroutine (similar concepts: procedure, function)
- Saving and appending data to a file
- Importance of file permissions
- Possible additional issues to deal with files: concurrency (race conditions), efficiency
- Alternatives: using databases, server or file-based

13 / 13